General Description

The WSF50P10 is the highest performance trench P-ch MOSFET with extreme high cell density , which provide excellent R_{DSON} and gate charge for most of the synchronous buck converter applications .

The WSF50P10 meet the RoHS and Green Product requirement,100% EAS guaranteed with full function reliability approved.

Product Summery

BVDSS	RDSON	ID
-100V	32mΩ	-34A

Applications

● Power Management for Industrial DC / DC Converters.

Features

- Advanced high cell density Trench technology
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- 100% EAS Guaranteed
- Green Device Available

TO-252-2L Pin Configuration





Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	-100	V
V_{GS}	Gate-Source Voltage	±20	V
I_D@T_C=25℃	Continuous Drain Current, $-V_{GS}$ @ -10V	-34	A
I_D@T_C=100℃	Continuous Drain Current, $-V_{GS}$ @ -10V	-22	A
I_{DM}	Pulsed Drain Current	-136[a]	A
E_{AS}[c]	Single Pulse Avalanche Energy	182	mJ
I_{AS}[c]	Avalanche Current	-27	A
P_D@T_C=25℃	Total Power Dissipation	96	W
T_{STG}	Storage Temperature Range	-55 to 150	℃
T_J	Operating Junction Temperature Range	-55 to 150	℃

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$[b]	Thermal Resistance Junction-Ambient	---	60	℃/W
$R_{\theta JC}$	Thermal Resistance Junction-Case	---	1.3	℃/W

Note a：Pulse width is limited by max. junction temperature.
Note b：Surface Mounted on 1in^2 pad area.
Note c：UIS tested and pulse width are limited by maximum junction temperature 150°C(initial temperature T_J=25°C).

Electrical Characteristics (T_J=25 ℃, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V , I_D=-250uA	-100	---	---	V
$\triangle BV_{DSS}/\triangle T_J$	BV_{DSS} Temperature Coefficient	Reference to 25℃ , I_D=-1mA	---	-0.021	---	V/℃
$R_{DS(ON)}$[d]	Static Drain-Source On-Resistance	V_{GS}=-10V , I_D=-18A	---	32	40	mΩ
		V_{GS}=-4.5V , I_D=-10A	---	38	51	
$V_{GS(th)}$	Gate Threshold Voltage	V_{GS}=V_{DS} , I_D =-250uA	-1.0	-2.0	-3.0	V
$\triangle V_{GS(th)}$	$V_{GS(th)}$ Temperature Coefficient		---	4.08	---	mV/℃
I_{DSS}	Drain-Source Leakage Current	V_{DS}=-80V , V_{GS}=0V , T_J=25℃	---	---	-1	uA
		V_{DS}=-80V , V_{GS}=0V , T_J=85℃	---	---	-30	
I_{GSS}	Gate-Source Leakage Current	V_{GS}=±20V , V_{DS}=0V	---	---	±100	nA
Q_g[e]	Total Gate Charge	V_{DS}=-30V , V_{GS}=-10V , I_D=-18A	---	56	---	nC
Q_{gs}[e]	Gate-Source Charge		---	9.5	---	
Q_{gd}[e]	Gate-Drain Charge		---	14.5	---	
$T_{d(on)}$[e]	Turn-On Delay Time	V_{DD}=-30V , V_{GS}=-10V , R_G=6Ω, I_D=-1A ,RL=30Ω.	---	9	---	ns
T_r[e]	Rise Time		---	17	---	
$T_{d(off)}$[e]	Turn-Off Delay Time		---	34	---	
T_f[e]	Fall Time		---	83	---	
C_{iss}[e]	Input Capacitance	V_{DS}=-50V , V_{GS}=0V , f=1MHz	---	2480	3207	pF
C_{oss}[e]	Output Capacitance		---	268	---	
C_{rss}[e]	Reverse Transfer Capacitance		---	126	---	

Diode Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current	VG=VD=0V , Force Current	---	---	-18	A
V_{SD}	Diode Forward Voltage	V_{GS}=0V , I_S=-18A , T_J=25℃	---	---	-1.2	V

Note d：Pulse test ; pulse width≤300μs, duty cycle≤2%.
Note e：Guaranteed by design, not subject to production testing.

Typical Characteristics

Power Dissipation



Drain Current



Safe Operation Area



Thermal Transient Impedance



Output Characteristics



Drain-Source On Resistance



Gate-Source On Resistance



Gate Threshold Voltage



Drain-Source On Resistance



Source-Drain Diode Forward



Capacitance



Gate Charge



Transfer Characteristics



Packaging information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.635	0.770	0.025	0.030
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830 REF.		0.190 REF.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.712	10.312	0.382	0.406
L1	2.900 REF.		0.114 REF.	
L2	1.400	1.700	0.055	0.067
L3	1.600 REF.		0.063 REF.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.250 REF.		0.207 REF.	

Attention

1, Any and all Winsok power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your Winsok power representative nearest you before using any Winsok power products described or contained herein in such applications.

2,Winsok power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Winsok power products described or contained herein.

3, Specifications of any and all Winsok power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

4, Winsok power Semiconductor CO., LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

5,In the event that any or all Winsok power products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

6, No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of Winsok power Semiconductor CO., LTD.

7, Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. Winsok power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

8, Any and all information described or contained herein are subject to change without notice due to product/technology improvement,etc. When designing equipment, refer to the "Delivery Specification" for the Winsok power product that you Intend to use.

9, this catalog provides information as of Sep.2014. Specifications and information herein are subject to change without notice.